

Durable, Reliable, High-Volume

Our debut production printer is designed for speed, reliability, and affordability. Produce up to 1 million A4 impressions per month and personalise them with variable data. Built with top-quality Kyocera printheads and long-life components for easy operation and maintenance, this highly reliable device will meet all your high-volume printing, scanning, and copying needs.



TASKalfa Pro 15000c



High Speed Inkjet Printer

150 ppm for A4 Simplex

600 x 600 dpi resolution

Specifications

BASIC SPECIFICATIONS

KYOCERA High Speed Inkjet Colour Multifunctional

Engine speed (Pages per minute):

Colour/Black – A4: 150ppm, Letter: 146 ppm, Legal/

B4: 98 ppm, A3: 88ppm, Ledger: 86 ppm, SRA3:

75ppm (print only), 12" x 18": 74 ppm (print only)

Warm-up time: 120 seconds or Less (Power On),

[W/DE-9100: 15 minutes or less]

First Page Out:

Copy: 5.0 Seconds or Less Black, 5.0 Seconds or Less Colour.

Print: 5.5 Seconds or Less Black, 5.5 Seconds or Less Colour

Resolution: 600 x 600 dpi; 600 x 1200 dpi

Memory/Hard Disk Drive: 4.5 GB RAM/

32 GB SSD/1 TB HDD Standard

Duplex: Standard Stackless Duplex Supports A5/

Statement to SRA3/12" x 18", 60 – 300gsm

Standard Output Tray: A5R/Statement –

13" x 19.2"/500 Sheets, (A6R : Right output tray)

Typical Electricity Consumption (TEC):

6.3 kWh/week [120V/220V]

Integrated accounting:

Dimensions (W x D x H): 965 mm x 740 mm x 1220 mm.

Weight: 308 kg or less.

Maximum Monthly Duty Cycle: 1,000,000 Pages per Month

PAPER SUPPLY

Standard Paper Source: Dual 500 Sheet Trays, Dual 1,500

Sheet Trays, 150 Sheet MPT, Auto Selection/Switching

Optional Paper Sources: Dual 2,440 Sheet (PF-9100)

Max 2 units 550 Sheet Multi-Media Paper Feeder (PF-9110)

Paper Capacity: Standard: 4,150 Sheets; Maximum: 14,310 Sheets

Paper Size: Tray: A5/5.5" x 8.5" – 12" x 18";

MPT: A6/5.5" x 8.5" – 13" x 19.2"

Paper Weight: Trays/(MPT) : Max 360gsm/(Max 300gsm)

Input Materials: Plain paper// plain paper// matte paper// Thick

paper//Postcard//Tab paper//Envelope//Banner paper// media

COPY FUNCTIONS

Max. original size: A3/Ledger

Continuous copying: 1 – 9,999

Zoom range: 25 – 400% in 1% steps

Preset magnification ratios: 5 Reductions/5 Enlargements

Exposure mode: Auto, manual: 16 steps

Image adjustments: Text + Photo, Photo, Text, Map,

Printed document

Features: Scan-once-copy-many, electronic sort, 2in1,

4in1, image repeat, page numbering, cover mode, booklet

copy, interrupt copy, form overlay, margin shift, auto

cassette change, Skip blank page, ID card copy

SCAN FUNCTIONS

Functionality: Scan-to-email, Scan-to-FTP, Scan-to-SMB 3.0,
Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan
(WIA Driver Network)

Scan speed: (A4, 300 dpi, Dual Scan) 220 images per minute;

(A4, 300 dpi, Simplex Scan) 120 images per minute

Scan resolution: 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi,

200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi; 256 greyscales

per colour

Max. scan size: A3, Ledger, Banner up to 2,200 mm

Original recognition: Text, photo, text + photo, light text//

fine line, optimised for OCR

File types: TIFF, PDF, PDF/A, JPEG, Open XPS, Encrypted

PDF, High compression PDF, PDF/A-1a/b, PDF/A-2a/b/u,

Features: Colour scan, Auto Colour Select, integrated

address book, Active Directory support, encrypted data

transfer, multi send (e-mail, fax, SMB/FTP folder, print)

at once, Blank page skip, Specified colour removal

OPTIONAL LARGE PAPER CAPACITY TRAY PF-9100

Dimensions (W x D x H): 330 x 730 x 1000 mm

Weight: 60kg or less

Power Consumption: Less than 860 W

Paper Size: A6/5.5" x 8.5" – 13" x 19.2"

Paper Capacity: 4,880 sheets (2,440 sheets per tray)

Paper Weight: 56 – 360gsm

OPTIONAL LARGE PAPER CAPACITY STACKER ST-9100

Dimensions (W x D x H): 900x 730 x 1000 mm

Weight: 120kg or less

Power Consumption: Less than 144 W

Paper Size: 330.2 x 487.9 mm(13x19.2) – A6R//Postcard"

Paper Capacity: 5,000 sheets

Paper Weight: 56 – 360gsm

PRINT SPECIFICATIONS

Standard Controller: QorIQ T1042 (Quad Core)/1.2GHz

PDLs/Emulations: PCL6 (PCL-XL/PCL5c), KPDL3

(P3), PDF, OpenXPS, XPS, PPML

Print Resolution: Up to 600 x 1200 dpi

Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap.

OS Compatibility: Windows: XP/Vista/7/8/8.1/10/Server

2003/Server 2008/Server 2008 R2/ Server 2012/Server

2012 R2; Novell NetWare 3.x/4.x/5.x/6.x; Mac OS 4.1.x;

Solaris 2.x; AIX; HP-UX; (LPR)OS 10.x; AirPrint Enabled.

Interfaces: Standard: 10/100/1000BaseTX,

Hi-Speed USB 2.0, 4 USB Host Interfaces

Network Print and Supported Protocols: TCP/IP, FTP, LPR,

NetBEUI, IPv4, IPv6, IPsec, SSL, HTTP, LPD, IPP, RawPort, LLTD,

SNTP, DHCP, SMTP, POP3, DNS, SNMPv1/v2, WSD Scan/Print

Drivers: KX Driver

OPTIONAL FIERY CONTROLLER PRINTING SYSTEM 50

Fiery System Version: Fiery FS300 Pro

Configuration: External

Memory: 16GB (8GB x 2)

CPU: Intel I7-6700 (3.4 GHz up to 40 GHz with turbo)

HDD: 1 TB SATA

FIERY INCLUDED OPTIONS

Fiery Spot On, Fiery Hot Folders, Virtual Printers,

Fiery Go, Papercut Compatibility, Paper Catalog,

Fiery JobFlow Base, Fiery Calibrate

CONSUMABLES

Average continuous Ink yield in accordance with
5% coverage A4.

IK-7115K, IK-7115C, IK-7115M, IK-7115Y

Staples: SH-10 for BF-9110, SH-14 for DF-7130

ENHANCEMENTS

PF-9100: Vacuum Feed Paper Feeder

PF-9110: Multi Bypass Tray

DE-9100: Drying & Decurl Unit

ST-9100: High Capacity Stacker

DF-9100: Document Finisher

BF-9110: Booklet Finisher

SL-9100: Status Indicator Light

PH-7C: Hole Punch

AK-9110: Relay Unit between Paper Feeder and Printer

AK-9120: Relay Unit between Stacker and Finisher

AK-9130: Relay unit between PF-9100 & 2nd PF-9100

AK-9140: Relay kit for PF-9110

When printing in large quantities, reliability is just as important as speed. The TASKalfa Pro 15000c combines both to help organisations maximise productivity while minimising operating costs and energy consumption. With the personalisation capabilities of digital and a variety of finishing options, our most powerful device yet has everything you need to cover your production printing needs.



KYOCERA Document Solutions Partner

OCTOBER2019DSTASKALFAPRO15000C/VER1.0

KYOCERA Document Solutions Europe B.V.
Bloemlaan 4, 2132 NP Hoofddorp, The Netherlands
Tel +31 (0) 20-654-0000 – Fax +31 (0) 20-653-1256



kyoceradocumentsolutions.eu

Kyocera Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.